

CE	c <b>FN</b> us	UK CA	ROHS	CONFLICT MINERAL FREE	ISO PUP IN	OUPTOURA OF
COST	T-EFFECTIVE	0	VERSATILE MEASURING	COMPACT FORMAT	é	DETACHABLE CONNECTOR

The digital panel meter **N1040i** combines in one compact and convenient 1/16 DIN enclosure, a high precision microprocessor based analog circuit with a very simple configuration interface to monitor a wide range of analog variables.

This low cost tough versatile indicator is compatible with most common thermocouples, Pt100 RTD and linear as 4 to 20 mA and mV.

With a intuitive interface to program range and decimal point through the keypad, **N1040i** allows inexperienced instrumentation operators easy installation and start up for most processes.

Optionally N1040i has two alarm relays with 6 programmable functions and auxiliary power supply for external signal conditioners.

How t	o Specify								
N1040i-	USB								
			0				100 to 240 Vac / dc power supply		
						24 V	Power supply 12 t	o 24 Vdc / 24 Vac	
			O		No communication				
				RS485	Modbus communica	ation			Di - EN
	o	RR	Two relays						FL. N1040i
		RA	One relay and one analog output 0-20 / 4-20 mA						1
		RE	One relay and one auxiliary 24 Vdc source						20230228

EDM Ltd. โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625 Email : contact@edm.co.th LINE : EDM9824

