



# Load Cell Panel Meter

## N1500-LC



- High responsiveness to process variable
- Allows visual acuity at a distance
- Timer function for safety alarms
- 30-point linearization for non-standard sensors

**N1500-LC** digital panel meter is the ideal tool for monitoring the analog variables of industrial processes that require an indicator for their load cells.

**N1500-LC** digital panel meter is quick and easy to configure via its front keyboard and is compatible with most load cell electrical signals, such as 0 to 20 mV, -20 to 20 mV, 0 to 50 mV, 0 to 20 mA, and 4 to 20 mA.

**N1500-LC** digital panel meter has a keyboard-programmable scale, a configurable decimal point feature, a 10 V power supply for powering the load cell, and a display that is easy to read. It's powered by a switch-mode power supply, and, in addition, the device has up to 4 alarm relays, a function for retransmitting the measured variable from 4 to 20 mA and supports RS485 digital communication with Modbus protocol.



**DESIGNED FOR HIGH-RESOLUTION VIEWING**



### FAST SAMPLING RATE

Ideal for dynamic processes



### TARE FUNCTION

It allows a more accurate weighing.



### DESIGNED FOR LOAD CELLS

Compatible with most common signals



### PROTECTION AND SAFETY

Anti-flame material  
UL94 V-2



### CUSTOM LINEARIZATION

30-point for non-standard sensors

<b>Display</b>	7-segment LED, 6-digit with 17 mm height
<b>Input Type</b>	4-20 mA, 0-20 mA, 0-50 mV, 0-20 mV and -20 to 20 mV
<b>Accuracy</b>	0,2 % of span
<b>Input impedance</b>	0-50 mV >10 MΩ 0-20 mA, 4-20 mA: 15 Ω (+2 Vcc @ 20 mA)
<b>Sampling rate</b>	15 samples per second
<b>Resolution</b>	Internal Resolution: 128000 levels Display Resolution: 62000 levels
<b>Custom Linearization</b>	30 points for non-standard sensors
<b>Digital Input</b>	Operates as a key for Hold, Peak Hold and maximum/minimum reset
<b>Analog Output</b>	0-20 mA or 4-20 mA (optional) - electrically isolated
<b>Alarms</b>	Up to 4 alarms
<b>Alarm Types</b>	Minimum, maximum, minimum differential, maximum differential, differential out of range, differential within range, and open sensor
<b>Timer Function</b>	Alarms with delay, pulse or oscillator timing
<b>Auxiliary Power Supply</b>	10 Vdc (or 5 Vdc) for powering load cells

<b>Optional</b>	2 relays, analog output (4-20 mA or 0-20 mA), RS485
<b>Communication</b>	RS485 Modbus RTU optional
<b>Math Function</b>	hold, peak hold, tare, zero tare and auto zero
<b>Safety</b>	Password protected configuration
<b>Configuration Interface</b>	Via RS485
<b>Power Supply</b>	100-240 Vac/dc or 12-24 Vdc
<b>Maximum Consumption</b>	7.5 VA
<b>Dimensions</b>	96 x 48 x 92 mm (1/8 DIN)
<b>Front Panel</b>	IP65 Polycarbonate (PC) UL94 V-2
<b>Enclosure</b>	IP20 ABS + PC UL94 V-0
<b>Operating Conditions</b>	5 to 50 ° C, and 0 to 80% RH up to 30 ° C
<b>Approvals</b>	CE, UL cUL and UKCA

20220830 - FL-N1500-LC - EN